



LX-E SANDER KIT WITH SMART 1600 VACUUM CLEANER

Reference 5510

DESCRIPTION

Kit consisting of the LX-E Giraffe Sander and the SMART 1600

Vacuum Cleaner.

Ceiling and wall sander equipped with a motor. 850 watts. Self-priming - vacuums up to 90% of debris, eliminating the need for a separate vacuum cleaner.

The Nauber SMART 1600 vacuum cleaner is a lightweight and compact vacuum cleaner for professional use, ideal for vacuuming dust and liquids.



CHARACTERISTICS

LX-E Giraffe Sander

Pear-shaped drive system with electronic speed adjustment, ranging between 900 RPM a 2.300 RPM.

Articulated dust extraction base with 6 holes for better dust suction and sanding performance. Includes a 1m long extension cable. Equipped with a high-power LED light strip. Includes a dust collection bag with a capacity of up to 30 liters.

220V / 50-60Hz equipment.

SMART 1600 VACUUM CLEANER

Equipped with a 1600W motor, AUTO-START system (the vacuum cleaner will automatically turn on when connected), and AUTO-CLEAN system (automatic filter cleaning at programmed intervals) maintaining constant suction power and extending the equipment's lifespan. It has a 30-liter capacity reservoir. Includes a remote control. Features a handle and locking casters for easy transport. Low noise level. Compact and easy to carry.

220 volts/50-60Hz equipment.

	HEIGHT	LENGTH	WIDTH
PACKAGING MEASUREMENTS 01	22cm	1.2m	27,5cm
PACKAGING MEASUREMENTS 02	64,5cm	45,8cm	37,5cm

INDICATIONS FOR USE

Ideal for sanding joint compound, acrylic filler, plaster, masonry, wood, finishing compounds, and general decorative effects.

ADDITIONAL DATA		
GROSS WEIGHT	22,39kg	
GEFADOR/TRANSFORMADOR	5kVA	

















LX-E SANDER KIT WITH SMART 1600 VACUUM CLEANER

Reference 5510

LX-E Giraffe Sander

ADDITIONAL DATA			
ENGINE POWER	850W		
ROTATION	900 - 2.300 RPM		
BASE DIAMETER	225mm		
NET WEIGHT	4,15kg		
GROSS WEIGHT	6,2kg		
VOLTAGE	220V - 50/60Hz		
GENERATOR/TRANSFORMER	2 kVA		





SMART 1600 Vacuum Cleaner

ADDITIONAL DATA		
ENGINE POWER	1600W	
SUCTION POWER	25 kPa	
POT. NOMINAL TOMADA AUX.	2000W	
FLOW RATE	1.7m³/min.	
PROTECTION CLASS	IPX4	
NOISE	82dB	
NET WEIGHT	12.75Kg	
GROSS WEIGHT	16,19kg	
VOLTAGE	220V - 50/60Hz	
GENERATOR/TRANSFORMER	3kVA	



