



**ROTO-6X SANDER KIT WITH APN-1600 VACUUM CLEANER** 

## **DESCRIPTION**

Reference 5461

Kit consisting of the **ROTO-6X Brushless Sander** and the **APN-1600 Vacuum Cleaner**.

\_\_\_\_\_

Roto-orbital sander with brushless motor.

Equipped with a 350-watt motor.

Electronic speed adjustment, ranging from 4,000 RPM to 10.000 RPM.

-----

The Nauber APN-1600 vacuum cleaner is a lightweight and compact vacuum cleaner for professional use, ideal for vacuuming dust and liquids.

#### **CHARACTERISTICS**

### **ROTO-6X Brushless Sander**

Braking assistance system with a swivel on the suction hose, ensuring greater safety and control.

Integrated electronic stabilizer, maintaining rotation. constant even under load.

Working memory, which stores the last configuration. speed used.

6"/150mm multi-hole base plate, optimizes dust extraction and improves finish.

Eccentricity rate of 5mm, ideal for efficient and uniform sanding.

5m power cord, removable via direct plug, offering greater reach, convenience and easy replacement.

### 220V / 50-60Hz equipment.

## **APN-1600 Vacuum Cleaner**

Made from high-strength plastic material. Equipped with a 1600W motor, auto-start system (when the connected device is

	HEIGHT	LENGTH	WIDTH
PACKAGING MEASUREMENTS	60cm	84cm	47,5cm

plugged in, the vacuum cleaner will automatically turn on). It has a 30-liter capacity dustbin. It features a handle and wheels for easy transport.

## 220V / 50-60Hz equipment.

## **INDICATIONS FOR USE**

Ideal for sanding joint compound, acrylic filler, plaster, masonry, wood, finishing compounds, and general decorative effects.

ADDITIONAL DATA		
GROSS WEIGHT	21,85kg	
GENERATOR/TRANSFORMER	5kVA	

















# **ROTO-6X SANDER KIT WITH APN-1600 VACUUM CLEANER**

Reference 5461

## **ROTO-6X Brushless Sander**

ADDITIONAL DATA		
ENGINE POWER	350W	
ROTATION	4.000-10.000 RPM	
ECCENTRICITY RATE	5mm	
BASE DIAMETER	150mm/6"	
NET WEIGHT	1.23kg	
VOLTAGE	220V - 50/60Hz	
GENERATOR/TRANSFORMER	2kVA	





## **APN-1600 Vacuum Cleaner**

ADDITIONAL DATA		
ENGINE POWER	1600W	
SUCTION POWER	20 kPa	
POT. NOMINAL TOMADA AUX.	2000W	
FLOW RATE	1.6m³/min.	
PROTECTION CLASS	IPX4	
NOISE	82dB	
NET WEIGHT	13,5Kg	
VOLTAGE	220V - 50/60Hz	
GENERATOR/TRANSFORMER	3kVA	











