



ROTO-9X SANDER KIT WITH APN-1600 VACUUM CLEANER

Reference 5462

DESCRIPTION

Kit consisting of the ROTO-9X Brushless Sander and the APN-1600 Vacuum Cleaner.

Roto-orbital sander with brushless motor. Equipped with a 400-watt motor. Electronic speed adjustment, ranging from 4,000 RPM to 8,500 RPM.

The Nauber APN-1600 vacuum cleaner is a lightweight and compact vacuum cleaner for professional use, ideal for vacuuming dust and liquids.

CHARACTERISTICS

ROTO-9X BRUSHLESS SANDER

Rotary-orbital system, providing uniform and efficient sandin

Optimized design for suction, developed for

Use with an external vacuum cleaner.

Multi-hole plate that enhances dust extraction and increases the efficiency of sandpaper.

No side bristles, greater suction efficiency.

and quality in the finish.

Brushless motor (without earbon brushless motor)

Brushless motor (without carbon brushes), larger service life and reliability.

Super flexible hose with a reach of up to 4 m.

Carrying and storage bag.

220V / 50-60Hz equipment.

APN-1600 Vacuum Cleaner

Made from high-strength plastic material.

Equipped with a 1600W motor,

auto-start system (when the connected

device is plugged in, the vacuum cleaner will automatically turn on). It has a 30-liter capacity dustbin. It features a handle and wheels for easy transport.

PACKAGING MEASUREMENTS 01

PACKAGING MEASUREMENTS 02

220V / 50-60Hz equipment.

INDICATIONS FOR USE

Ideal for sanding joint compound, acrylic filler, plaster, masonry, wood, cementitious and finishing compounds.

ADDITIONAL DATA		
GROSS WEIGHT	18kg	
GENERATOR/TRANSFORMER	5kVA	



HEIGHT

19.75cm

59cm



LENGTH

153cm

84cm



WIDTH

26cm

48cm











ROTO-9X SANDER KIT WITH APN-1600 VACUUM CLEANER

Reference 5462

ROTO-9X BRUSHLESS SANDER

ADDITIONAL DATA		
ENGINE POWER	400W	
ROTATION	4.000-8.500 RPM	
Eccentricity rate	4mm	
BASE DIAMETER	225mm	
NET WEIGHT	3,2kg	
VOLTAGE	220V - 50/60Hz	
GENERATOR/TRANSFORMER	2kVA	



APN-1600 Vacuum Cleaner

ADDITIONAL DATA		
ENGINE POWER	1600W	
SUCTION POWER	20 kPa	
POT. NOMINAL TOMADA AUX.	2000W	
FLOW RATE	1.6m³/min.	
PROTECTION CLASS	IPX4	
NOISE	82dB	
NET WEIGHT	13,5Kg	
VOLTAGE	220V - 50/60Hz	
GENERATOR/TRANSFORMER	3kVA	



