



TECHNICAL SHEET

OPERATIONAL DATA

FT ROTO-5E/LX-E/APN-1600 - 4738
Elaboration date: 08/13/2025
Revision: 10/21/2025-01

NAUBER[®]

MAQUINAS

ROTO-5E SANDER KIT + LX-E SANDER + APN-1600 VACUUM CLEANER

Reference 4738

DESCRIPTION

Kit consisting of the **ROTO-5E Brushless Sander**, the **LX-E Sander**, and the **APN-1600 Vacuum Cleaner**.

Roto-orbital sander with brushless motor.

Equipped with a 350-watt motor.

Digital panel with electronic speed adjustment, ranging from 4,000 RPM to 10,000 RPM.

Nauber LX-e ceiling and wall sander equipped with an 850-watt motor.

Self-priming - vacuums up to 90% of debris, eliminating the need for a separate vacuum cleaner.

The Nauber APN-1600 vacuum cleaner is a lightweight and compact vacuum cleaner for professional use, ideal for vacuuming dust and liquids.



	HEIGHT	LENGTH	WIDTH
PACKAGING MEASUREMENTS	84cm	115cm	49cm

CHARACTERISTICS

ROTO-5E Brushless Sander

Integrated electrical stabilizer. Working memory (stores the last speed setting). 6" / 150mm diameter base plate with multi-hole pattern.

Approximate weight of 1.45 kg (without power cord). Power cord is 5 meters long.

220V / 50-60Hz equipment.

LX-E sander

Pear-shaped drive system with electronic speed adjustment, ranging from 900 RPM to 2,300 RPM. Articulated suction base with 6 holes for better dust suction and sanding performance. Includes a 1m long extension cable. Equipped with a high-power LED light strip. Includes a dust collection bag with a capacity of up to 30 liters.

220V / 50-60Hz equipment.

APN-1600 Vacuum Cleaner

Made of high-resistance plastic material. Equipped with a 1,600W motor and an auto-start system (the vacuum cleaner will automatically turn on when the device is connected). Features a 30-liter capacity dustbin. Includes a handle and wheels for easy transport.

220V / 50-60Hz equipment.

INDICATIONS FOR USE

Ideal for use in construction or for general cleaning.



Assembled in
Brazil



CREA-SC
Record
172951-7



Email

atendimento@nauber.com.br



Telephone

+55 47 33745969



Web Site

www.nauber.com.br



TECHNICAL SHEET

OPERATIONAL DATA

FT ROTO-5E/LX-E/APN-1600 - 4738
Elaboration date: 08/13/2025
Revision: 10/21/2025-01

NAUBER[®]

MAQUINAS

ROTO-5E SANDER KIT + LX-E SANDER + APN-1600 VACUUM CLEANER

Reference 4738

ROTO-5E BRUSHLESS SANDER



ADDITIONAL DATA	
ENGINE POWER	350W
ROTATION	4.000-10.000 RPM
ECCENTRICITY	5mm
BASE DIAMETER	6" / 150mm
NET WEIGHT	1,65kg
VOLTAGE	220V - 50/60Hz
GENERATOR/TRANSFORMER	2kVA

LX-E sander

ADDITIONAL DATA	
ENGINE POWER	850W
ROTATION	900 - 2.300 RPM
BASE DIAMETER	225mm
NET WEIGHT	4,15kg
VOLTAGE	220V - 50/60Hz
GENERATOR/TRANSFORMER	2 kVA



APN-1600 Vacuum Cleaner

ADDITIONAL DATA	
ENGINE POWER	1600W
SUCTION POWER	20 kPa
POT. NOMINAL TOMADA AUX.	2000W
FLOW RATE	1.6m ³ /min.
PROTECTION CLASS	IPX4
NOISE	82dB
NET WEIGHT	13,5Kg
VOLTAGE	220V - 50/60Hz
GENERATOR/TRANSFORMER	3kVA

ADDITIONAL DATA	
GROSS WEIGHT	24,45kg
GENERATOR/TRANSFORMER	7kVA



Assembled in
Brazil



CREA-SC
Record
172951-7



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br