



TECHNICAL SHEET

OPERATIONAL DATA

FT ROTO-5E - 3666
Elaboration date: 08/28/2024
Revision: 05/24/2025-02

NAUBER[®]

MAQUINAS

ROTO-5E ORBITAL BRUSHLESS SANDER

Reference 3666

DESCRIPTION

Roto-orbital sander with brushless motor.
Equipped with a 350 Watt motor.
Digital panel with electronic speed adjustment,
ranging from 4,000 RPM to 10,000 RPM.

FEATURES

Integrated electric stabilizer.
Working memory (stores the last worked speed
setting). 6" / 150mm diameter base plate with
multi-hole pattern. Approximate weight of 1.45 kg
(without power cable). 5 meter long power cable.

220V / 50-60Hz Equipment.



**STANDARD BASE 6" 150mm
MULTI-HOLE STANDARD**



**FOLLOWS
CARRYING BAG**



**LED INDICATOR
OF SPEED**

INDICATIONS FOR USE

Suitable for sanding masonry walls, plaster, putty, acrylic putty, finishing cement putties, wood line, metal line and automotive line.

ADDITIONAL DATA	
POWER	350W
ROTATION	4.000-10.000 RPM
ECCENTRICITY	5mm
BASE DIAMETER	6" / 150mm
NET WEIGHT	1,65kg
GROSS WEIGHT	2,4kg
GENERATOR/TRANSFORMER INDICATION	2 kVA

	HEIGHT	LENGTH	WIDTH
EQUIPMENT DIMENSIONS	17cm	36cm	16cm



**Assembled in
BRAZIL**



CREA-SC
Record
172951-7



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br