



TECHNICAL SHEET

OPERATIONAL DATA

FT TK200CG - 1000
Elaboration date: 02/11/2023
Revision: 11/12/2025-04



TK200CG LVLP TEFLON 600CC 1.5MM TAKAMATSU SPRAY GUN

Reference 1000

DESCRIPTION

The NAUBER TK200CG LVLP spray gun offers excellent ergonomics, is lightweight, and easy to operate.

High durability under high production conditions makes the TK200CG LVLP a differentiated product.

Featuring an LVLP painting system, it offers excellent finish quality and high performance designed for high-volume production.

BENEFITS:

Fog reduction

- It increases productivity.
- Application speed
- Minimum maintenance cost
- High-Transfer System
- Very light
- Low air consumption
- Ergonomic design
- Easy to use
- Fast amortization



CHARACTERISTICS

Sistema LVLP.

Stainless steel body with balanced air cap.

Machined Teflon seals. Easy maintenance.

Nozzle and needle made of highly durable material. The TAKAMATSU TK200CG spray gun comes equipped with a 1.5 nozzle and needle and an air cap with an LVLP system, allowing for reconfiguration to the LVLP system or nozzle and needle replacement for other scoring levels.

Includes disassembly wrench and cleaning brush.

PACKAGING MEASUREMENTS	HEIGHT	LENGTH	WIDTH
	23cm	16cm	13cm

INDICATIONS FOR USE

Furniture industry, metalworking, agricultural and road equipment, among others.

ADDITIONAL DATA

AIR CONSUMPTION	226 LITERS/MIN.
MAXIMUM PRESSURE	2 bar (29 PSI)
AVAILABLE TIPS	1.2mm / 1.8mm / 2.0mm
AIR CONNECTION	M 1/4" NPS
PRODUCT CONNECTION	M 3/8" NPS
CUP CAPACITY	600ml
GROSS WEIGHT	1,139kg



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br