



TECHNICAL SHEET

OPERATIONAL DATA

FT NAUBER TIP GUARDS
Elaboration date: 01/14/2023
Revision: 01/24/2026-06



AIRLESS NAUBER TIP GUARDS

Reference see below

NICKEL PLATED

DESCRIPTION

Tip guard with standard 7/8 nickel-plated thread.

CHARACTERISTICS

Compatible with airless tips with a stem diameter of 11,1mm. It withstands pressure up to 5.000 PSI.



Reference: 4549



Reference: 5422

ALUMINUM

DESCRIPTION

Tip guard with standard 7/8 aluminum thread.

CHARACTERISTICS

Compatible with airless tips with a stem diameter of 11,1mm. It withstands pressure up to 5.000 PSI.

STAINLESS STEEL

DESCRIPTION

Tip guard with standard 7/8 stainless steel thread.

CHARACTERISTICS

Compatible with airless tips with a stem diameter of 11,1mm. It withstands pressure up to 7.250 PSI.

Reference: 4230



Reference: 4229

UHD

DESCRIPTION

Tip guard with standard 7/8 stainless steel thread.

CHARACTERISTICS

Compatible with airless tips with a stem diameter of 11,1mm. It withstands pressure up to 7.250 PSI.

INSTRUCTIONS FOR USE (ALL MODELS)

For use in airless painting systems.

PACKAGING DIMENSIONS	HEIGHT	LENGTH	WIDTH
ALL MODELS	15,1cm	9cm	3,5cm

GROSS WEIGHT	
ALL MODELS	65g



CREA-SC
Record
172951-7



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br